



# ISUZU 'GRAFTER' N35.150(TT) 3.5T GVW

4X2 RIGID TWIN REAR WHEELS TIPPER

EURO 5


## UK STANDARD VEHICLE PLATED WEIGHTS

GVW **3500KG**  
GTW **7000KG\*†**



## UK AXLE DESIGN WEIGHTS

Front **1900KG**  
Rear **2000KG**



## WEIGHTS (KG)

### CAB TYPE

day

### WHEELBASE (WB)

2480

Vehicle Mass Unladen	Front Axle	1480
	Rear Axle	885
Total		2365
GVW		3500
Max. Permissible Trailer Weight		3500*
Payload		1135

## DIMENSIONS (mm)

Overall Length	OAL	4870
Overhang	Front FOH	1110
	Rear ROH	1380
Cab Gap	CB	130
C/L Front Axle to Rear of Cab	CA	430
Body Length	BL	3200
Overall Vehicle Width	OVW	1980
Chassis Frame Width		700
Body Width		1980
Height of Body Sides		400
Cab Width	OW	1770
Overall Height (Unladen)	OH	2140
Body Bed Height	EH	940
Minimum Road Clearance	HH	190
Track	Front AW	1475
	Rear CW	1425
Rear Axle Width	BW	1854

## BODY SPECIFICATION

- All steel tipper body with rear tailgate hinged top and bottom
- Steel safety prop
- Sheet steel body floor
- Full cab height contoured tubular steel headboard, lower half covered in 2mm mesh infill with full width cross bars. Ladder loops on top rail
- N/S body mounted foldable access ladder
- Side mounted rope hooks for easy load restraint
- Body, frame and underframe fully corrosion protected by electro-cathodisation process
- Underframe, frame, headboard, floor and pillars finished in Isuzu Gloss Black using electrostatic process
- Body sides finished in Isuzu Gloss Arc White using electrostatic paint process
- Spring locked flush fitting plastic latches
- 24V electro-hydraulic tipping pump system with underfloor scissor type ram and subframe
- High quality poly plastic rear wings and brackets

† If you intend operating regularly at 7 tonnes GTW refer to the Isuzu Truck (UK) Limited technical department before ordering. \* Driver licence and tachograph regulations apply.

N35.150(TT)/0909/GW/3K

1. Unladen weights exclude fuel, driver, spare wheel + carrier, tool kit and jack. (Tolerance +/- 3%).

2. Isuzu Truck (UK) Ltd. shall have no liability whatsoever should the information supplied have incorrect data, descriptions or illustrations.


**ISUZU**  
BUILT AROUND U

# ISUZU 'GRAFTER' 1500 (TT) 3.5T GVW

## 4X2 RIGID TWIN REAR WHEELS TIPPER

### EURO 5

## Mechanical Specification (standard equipment)



### Engine 4JJ1TC

- Isuzu turbo intercooled DOHC 4 cylinder diesel (Euro 4)

**Bore:** 95.4mm

**Stroke:** 104.9mm

**Capacity:** 2999cc

**Max Power:** 110kW

(150bhp) at 2800rpm

**Max Torque:** 375Nm between 1600-2800rpm

**Injection Type:** Common rail

**Euro 5 Compliance:**

EGR (Exhaust Gas Recirculation) with DPD (Diesel Particulate Defuser), Fuel cooler and OBD

### Fuel Tank

**Capacity:** 75 litres

### Transmission

- 5-speed synchromesh MYYST overdrive

• <b>Ratios:</b>	1st	5.315:1
	2nd	3.053:1
	3rd	1.655:1
	4th	1.000:1
	5th	0.721:1
	reverse	5.068:1

**Rear Axle Ratio:** 4.10:1

**Tyres:** 195/75 R16C radial, spare wheel and carrier

**Wheels:** Dual rear wheels 5.50J x 16, 5-stud

### Cab Exterior

- New aerodynamic Isuzu hexapod design white all steel cab
- Manual tilt to 45 deg
- Laminated windscreen
- Plastic resin non-slip entry steps
- 90 deg. opening cab doors
- Zinc galvanised cab frame structure
- 2 flush mounted halogen headlamps with side mounted indicators
- Front tyre mud guards with spray suppression
- Steel reinforced composite front bumper with fog lights
- Chrome radiator grille
- Keyless door entry and immobiliser

### Frame

Ladder type channel section straight side rails, riveted upper flanges

### Cooling

**Radiator:** Tube and fin type with fan and viscous clutch

### Clutch

300 mm diaphragm type with hydraulic actuation

### Cab Interior

- Flame resistant interior trim
- Vinyl floor matting
- Pillar mounted entrance grab handles both sides
- SRS air bags driver and passenger

### Seats (all cloth)

- Drivers fully adjustable with head restraint
- Dual passenger seat with folding back
- Driver and outer passenger retractable diagonal seat belts, with pre-tensioner
- Centre seat lap belt

### Vision

- Large foldable door mirrors
- Interior rear view mirror on collapsible mounting
- Driver and passenger sun visors
- Deep cut side windows to reduce blind spots
- Electric windows with driver control and lock

### Heating & Ventilation

- 4-speed blower
- Multiple cab vents

### Axles

**Front:** Reverse Elliott I-Beam

**Rear:** Banjo fully floating

### Suspension

**Front:** Parabolic alloy steel leaf springs and hydraulic shock absorbers

**Rear:** Parabolic alloy steel leaf springs with hydraulic double acting telescopic shock absorbers

### Steering

- Recirculating ball type with full integral hydraulic power assistance
- Tilt and telescopic steering column

### Brakes

**System:** Divided hydraulic servo-assisted with load sensing

**Front:** 293 mm ventilated discs with asbestos free pads

**Rear:** 275mm ventilated discs with asbestos free pads

**Park:** Mechanical drum brake rear of transmission

### Instruments

- Speedometer with odometer & trip
- Rev counter
- 9 Metre remote 'Wanderlead' tipper control stored in cab
- Gauges:** Fuel level and coolant temperature

### Switches & Electrical

- Steering column mounted combination switch for indicators, headlamps (high beam), side and headlamp, front and rear fog lights
- Wiper and washer (2-speed and intermittent)
- Exhaust brake
- Steering wheel horn switch
- Hazard lights
- Head lamp levelling
- Brake warning buzzer
- Interior light
- Key operation for quick cold start, start and stop
- Engine quick warm up
- Cigarette lighter
- Central locking
- Reverse warning buzzer in cab
- DPD engage
- Fast engine idle
- Chassis/battery mounted tipper system isolating switch

### Warning Lamps

- Battery charge
- Oil pressure
- Check brake system
- Low fuel
- Glow plug operation
- High beam and indicators
- Parking brake on
- Exhaust brake operation
- Fuel/water separator
- Check engine
- DPD engaged/warning
- Service warning
- OBD
- Front and rear fog lights
- Tipping system warning light

### Tool Kit

4000 kg jack, with a small selection of hand tools

### Radio

RDS Radio / CD Player package

### Storage Space

- Compartment box
- Centre console tray
- Door pockets
- Centre fascia pocket
- Pop out type cup holder
- Overhead roof shelves
- Card holder

### Ancillaries

**Starter:** Reduction type 24 V – 4.0 kW

**Alternator:** 24 V – 50 Amp

**Quick Start:** 4 glow-plugs on start relay

**Battery:** 2 x 12 V – 75 AH (maintenance free)

**Tipping System:** 24 V – pump with underfloor ram

### The following optional items are available:

- Isuzu Branded Mats
- Suspension Seat
- Satellite Navigation
- Reversing Aids
- Road Speed Limiter
- PTO Switch

For further information please contact your local dealer, ring us directly on **01707 28 29 30** or visit our website [www.isuzutruck.co.uk](http://www.isuzutruck.co.uk)